

SURTEC[®], Inc. Surface Technology

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

NC-125

NC-125

NEUTRAL pH CLEANER CONCENTRATE

DESCRIPTION:

NC-125 will clean polished floors without affecting the polish coating when used according to directions. NC-125 will rinse easily without excessive foaming. NC-125 may be used on all types of painted surfaces that are not affected by water. Effectively cleans woodwork, doors, commercial fixtures, vinyl upholstery, all plastic surfaces, etc. Do not use on unsealed cork or wood floors.

DIRECTIONS:

For moderately soiled floors and dirty wall cleaning, use 4 to 8 ounces NC-125 per gallon of water. For light floor and wall cleaning, use 1 to 2 ounces NC-125 per gallon of water. For cleaning all other surfaces, concentrations can be adjusted from 1 ounce per gallon of water depending on the amount and type of soil.

SPECIFICATIONS:

COLOR:	Blue
ODOR:	Mild
pH:	9.8 ± 0.2 (concentrate) 8.6 ± 0.2 (2% dilution with tap water)
HMIS RATING	Health = 1 Flammability = 0 Physical Hazard = 0
FLASH POINT:	None (C.O.C. Method)
SURFACE TENSION:	29 dynes per cm. (at 2 oz. per gallon dilution)
V.O.C. CONTENT:	Less than 0.25%
DILUTION USE RANGE:	1:10 to 1:128
DETERGENT TYPE:	Nonionic/anionic
BIODEGRADABLE:	Yes
SPECIFIC GRAVITY:	1.0
DENSITY:	8.34 pounds per gallon
SOLUBILITY IN WATER:	100% (hard, soft and/or deionized water)
SHELF LIFE:	Minimum 1 year from date of sale
FREEZE/THAW STABILITY:	Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES:	4 x 1 gallon jugs 5 gallon Twin Pack (2 x 2.5 gal. bottles/box) 55 gallon drums

rev. 3/7/03

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.