

SURTEC[®], Inc. Surface Technology

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

SYNERGY

SY-190

BUS, TRUCK & CAR WASH OIL AND GREASE REMOVER FOR CONCRETE AND ASPHALT

DESCRIPTION:

SYNERGY is a unique mixture of water borne detergents, surfactants and wetting agents which act upon the bonds that attach dirt, oil, and soils to surfaces, severing the bond and allowing the surface to be cleaned. This unique chemistry makes SYNERGY more effective than petroleum solvent based degreasers for oil and grease spot removal from concrete and asphalt, yet SYNERGY possesses no flammability, objectionable odors or other problems associated with petroleum solvents.

Although SYNERGY is strong enough to remove grease from concrete, with proper dilution it is mild enough to use for safe and effective vehicle cleaning. Used properly, SYNERGY leaves no residue, and will not streak vehicle paint or glass.

DIRECTIONS:

REMOVING OIL AND GREASE FROM CONCRETE AND ASPHALT - Apply SYNERGY undiluted to spot, agitate with a stiff brush, then allow to dwell for 10 to 20 minutes. After dwell, agitate again, then pressure wash or rinse with water and allow to dry.

EXTERIOR AND INTERIOR VEHICLE CLEANING - Use 2 to 4 ounces of SYNERGY per gallon of water. Agitate with a soft vehicle washing brush or cloth, rinse or pressure wash with clean water and allow to dry.

COSMOLINE REMOVAL FROM VEHICLES - Dilute 1 part SYNERGY with up to 4 parts water. Apply with soft vehicle washing brush or sprayer, let dwell 5 to 10 minutes, then rinse or pressure wash with clean water and allow to dry.

SPECIFICATIONS:

COLOR: Clear
ODOR: Mild
pH: 11.0 ± 0.2 (concentrate)
..... 10.2 ± 0.2 (5% dilution with water)
HMIS RATING Health =1 Flammability = 0 Physical Hazard = 0
FLASH POINT: None (C.O.C. Method)
SURFACE TENSION: 29 dynes per cm. (at 2 oz. per gallon dilution)
DILUTION USE RANGE: 1:64 to undiluted (see directions above)
DETERGENT TYPE: Nonionic/anionic
BIODEGRADABLE: Yes
SPECIFIC GRAVITY: 1.03
DENSITY: 8.5 pounds per gallon
SOLUBILITY IN WATER: 100% (hard, soft and/or deionized water)
SHELF LIFE: Minimum 2 years
FREEZE/THAW STABILITY: Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES: 4 x 1 gallon jugs
..... 5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
..... 55 gallon drums

rev. 3/7/03

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.