

SURTEC[®], Inc. Surface Technology

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

SURTEC[®] "CERTIFIED" GREEN

920 NON-BUTYL STRIPPER

ST-920

FLOOR POLISH STRIPPER CONCENTRATE

DESCRIPTION:

920 NON-BUTYL STRIPPER is a concentrated stripper and is not intended to be used as a general purpose cleaner. 920 NON-BUTYL STRIPPER is a balanced formula designed for fast, complete removal of polymeric floor finishes. 920 NON-BUTYL STRIPPER provides low foaming and easy rinsing. When used according to directions, 920 NON-BUTYL STRIPPER is safe to use on vinyl asbestos, pure vinyl, asphalt tile, terrazzo, cement and other similar surfaces. Do not use on cork or wood. If in doubt, consult SURTEC or pre-test in an inconspicuous area.

DIRECTIONS:

Dilute with up to 15 parts water for stripping most floor polishes. Dilute with 8 to 10 parts water for very difficult to remove floor polishes. Allow solution to dissolve and raise old polish for 5 to 10 minutes before scrubbing. LET 920 NON-BUTYL STRIPPER DO THE WORK FOR YOU. After scrubbing and pick up, rinse the floor and allow to dry. 920 NON-BUTYL STRIPPER's efficiency allows for much faster and complete stripping without the need for abrasive stripping pads. In most cases, light or medium scrub pads may be used.

SPECIFICATIONS:

COLOR: Yellow
ODOR: Citrus
pH: 14.0 (concentrate)
..... 12.5 ± 0.2 (1:10 dilution)
HMIS RATING Health =2 Flammability = 0 Physical Hazard = 0
FLASH POINT: None (C.O.C. Method)
DILUTION USE RANGE: 1:6 to 1:15
DETERGENT TYPE: Nonionic
SPECIFIC GRAVITY: 1.01
DENSITY: 8.4 pounds per gallon
SOLUBILITY IN WATER: 100% (hard, soft and/or deionized water)
SHELF LIFE: Minimum 1 year from date of sale
FREEZE/THAW STABILITY: Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES: 4 x 1 gallon jugs
..... 5 gallon Twin Pack (2 x 2.5 gal. bottles/box)

THE GREEN SYSTEM By Surtec[®]

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.