SURTEC, Inc. *Surface Technology*
1880 N MACARTHUR DR. TRACY, CA 95376 Phone (209) 820-3700 Fax (209) 820-3793

SURCO

SR-121

ALL PURPOSE CONCENTRATE
NEUTRAL pH CLEANER

DESCRIPTION:
SURCO will clean polished floors without affecting the polish coating when used according to directions. SURCO will rinse easily without excessive foaming. SURCO may be used on all types of painted surfaces that are not affected by water. Effectively cleans woodwork, doors, commercial fixtures, vinyl upholstery, all plastic surfaces, etc. Do not use on unsealed cork or wood floors. SURCO is also excellent for vehicle washing - strong enough to remove road tar, mild enough so that vehicle paint is not adversely affected, and rinses easily and streak-free.

DIRECTIONS:
For moderately soiled floors and dirty wall cleaning, use 2 to 4 ounces SURCO per gallon of water.
For light floor and wall cleaning, use 1 to 2 ounces SURCO per gallon of water.
For vehicle cleaning, use 2 to 4 ounces per gallon of water.
For cleaning all other surfaces, concentrations can be adjusted from 1 ounce per gallon of water depending on the amount and type of soil.

SPECIFICATIONS:

COLOR:	Yellow
ODOR:	Mild
pH:	9.8 + 0.2 (concentrate) 8.6 + 0.2 (2% dilution with tap water)
HMIS RATING	Health =1 Flammability = 0 Physical Hazard = 0
FLASH POINT:	None (C.O.C. Method)
SURFACE TENSION:	29 dynes per cm. (at 2 oz. per gallon dilution)
V.O.C. CONTENT:	Less than 0.25%
DILUTION USE RANGE:	1:10 to 1:128
DETERGENT TYPE:	Nonionic/anionic
BIODEGRADABLE:	Yes
SPECIFIC GRAVITY:	1.0
DENSITY:	8.3 pounds per gallon
SOLUBILITY IN WATER:	100% (hard, soft and/or deionized water)
SHELF LIFE:	Minimum 1 year from date of sale
FREEZE/THAW STABILITY:	Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES:	4 x 1 gallon jugs 5 gallon pails 55 gallon drums

⚠ WARNING: This product can expose you to chemicals including coconut oil diethanolamine condensate and diethanolamine, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

rev. 09/17/18
SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.