

SURTEC[®], Inc. *Surface Technology*

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

SUPER SCRUB

SS-217

HEAVY DUTY WATER BASE CLEANER/DEGREASER CONCENTRATE

DESCRIPTION:

SUPER SCRUB combines cleaning and degreasing without the use of petroleum solvents. It is a superior cleaner for aluminum, fiberglass, stainless steel, and most painted surfaces. Oxidized and sensitive paints may be affected so test a small area prior to use.

SUPER SCRUB is a versatile cleaner and is the product of choice for removing oily or greasy types of soils from concrete, stone and ceramic tile floors and surfaces, in areas such as vehicle repair shops, warehouses, industrial plants, etc.

DIRECTIONS:

For oil, grease and soil removal from cars, boats, planes and trucks, dilute each part of SUPER SCRUB with up to 6 parts of water.

For light, oily soils such as found in kitchens and food handling areas, SUPER SCRUB may be diluted with up to 15 parts of water. Follow with potable water rinse.

For concrete and stone tile floor cleaning, or floor polish stripping, add 16 to 32 ounces of SUPER SCRUB per gallon of water. Apply liberally to floor, allow ten minutes dwell time and scrub with floor machine equipped with a scrubbing or stripping pad or brush. Rinse well and allow to dry before opening to traffic or sealer/polish application.

SPECIFICATIONS:

COLOR:	Green
ODOR:	Pine
pH:	12.3 ± 0.1 (concentrate)
.....	11.3 ± 0.2 (1:10 dilution)
HMIS RATING	Health =1 Flammability = 0 Physical Hazard = 0
FLASH POINT:	None (C.O.C. Method)
DILUTION USE RANGE:	1:30 to 1:4
BIODEGRADABLE:	Yes
U.S.D.A. AUTHORIZED:	Yes
DETERGENT TYPE:	Nonionic
SPECIFIC GRAVITY:	1.01
DENSITY:	8.4 pounds per gallon
SOLUBILITY IN WATER:	100% (hard, soft and/or deionized water)
SHELF LIFE:	Minimum 1 year from date of sale
FREEZE/THAW STABILITY:	Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES:	4 x 1 gallon jugs
.....	5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
.....	55 gallon drums

rev. 12/1/04

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.