

# **SURTEC<sup>®</sup>, Inc.** *Surface Technology*

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

## **ULTRA STRIP<sup>™</sup>** ST-237 **SUPER CONCENTRATE FLOOR POLISH STRIPPER**

### **DESCRIPTION:**

ULTRA STRIP is the latest advance in floor finish stripper technology. ULTRA STRIP is formulated to quickly dissolve and emulsify polymer floor finishes, including ultra high speed floor finishes that have been burnished repeatedly over long periods of time. Because of this new technology, stripper use can be reduced substantially. ULTRA STRIP cuts through heavy build up quickly, eliminating the need to restrip repeatedly.

ULTRA STRIP is safe for use on vinyl composition tile, stone tile, concrete, terrazzo and other hard surface floors. It is also an excellent cleaner and degreaser for unsealed concrete, terrazzo, stone tile, and similar unfinished masonry surfaces. Do NOT use on wood or cork, rubber or asphalt tile or linoleum floors. Pre-test in an inconspicuous area; if in doubt consult SURTEC.

### **DIRECTIONS:**

Dilute with 20 to 30 parts water for stripping most floor finishes. Dilute with 10 to 15 parts water for heavy build-up. If stripping of a "non-strippable" or exterior water base seal is desired, pre-test in an inconspicuous area with a dilution of 6 to 10 parts water for each part ULTRA STRIP.

Allow solution to dissolve and emulsify old finish for 5 to 10 minutes before scrubbing. LET ULTRA STRIP DO THE WORK FOR YOU. After scrubbing and pickup, rinse the floor thoroughly with clean water and allow to dry before application of new seal and/or polish.

ULTRA STRIP's efficiency allows for much faster and complete stripping without the need for harsh, abrasive stripping pads. Because of the chemical strength of ULTRA STRIP, be sure to protect walls, coving, elevator doors, contiguous carpeting, etc. from splashing of stripping solutions.

### **SPECIFICATIONS:**

COLOR:	Clear
ODOR:	Citrus
pH:	14.0 (concentrate)
	12.8 ± 0.2 (1:20 dilution)
HMISRATING	Health = 2 Flammability = 1 Physical Hazard = 0
FLASH POINT:	Greater than 200° F. (C.O.C. Method)
DILUTION USE RANGE:	1:6 to 1:30
DETERGENT TYPE:	Nonionic
SPECIFIC GRAVITY:	1.0
DENSITY:	8.34 pounds per gallon
SOLUBILITY IN WATER:	100% (hard, soft and/or deionized water)
SHELF LIFE:	Minimum 1 year from date of sale
FREEZE/THAW STABILITY:	Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES:	4 x 1 gallon jugs
	5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
	55 gallon drums

rev. 3/7/03

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.