

SURTEC[®], Inc. *Surface Technology*

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

SUPER GLOSS

FP-517

HIGH GLOSS LOW MAINTENANCE FLOOR POLISH

DESCRIPTION:

SUPER GLOSS utilizes new, innovative polymer technology to achieve excellent gloss and maintain it for extra-long periods of time. It was formulated specifically to respond exceptionally well to maintenance with occasional high speed and ultra high speed buffing. SUPER GLOSS provides outstanding floor protection and appearance over extended periods of time, providing a savings in labor and materials. SUPER GLOSS exceeds the Coefficient of Friction safety standards of ASTM Designation D-2047.

DIRECTIONS:

FLOOR PREPARATION - If stripping is necessary, use SURTEC L.O.S. or SUPER STRIP according to label directions.

APPLICATION - Use standard application procedures with thin to medium coats of finish. Make sure polish is completely dry before applying subsequent coat or opening to traffic. As long as the polish is allowed to completely dry between coats, as many coats as needed may be applied consecutively.

MAINTENANCE - Use SURTEC LF-150 Heavy Duty Cleaner or FLOOR SHINE High Speed Floor Maintainer at 1 or 2 oz. per gallon of water for routine maintenance by damp mopping or scrubbing, and prior to high-speed buffing.

RECOAT - SURTEC LF-150 should be used for scrubbing prior to recoating. Scrub the floor with a low speed buffer or automatic scrubber and blue or green (medium scrub) pads using LF-150 at a dilution of 2 to 4 ounces per gallon of water. Rinse the floor with clean water and let dry before applying SUPER GLOSS.

SPECIFICATIONS:

COLOR: Milk white, dries clear.
ODOR: Sweet
pH: 8.4 ± 0.2
HMIS RATING Health =1 Flammability = 0 Physical Hazard = 0
REFRACTOMETER SOLIDS: 22%
FLASH POINT: None (C.O.C. Method)
GLOSS: 95 (A.S.T.M. Test D-523, 60°)
TYPE OF POLYMER: Acrylic, metal interlock
COVERAGE (can vary with type of floor and application method):
..... 2000 sq. ft. per gallon (average coverage on a sealed floor)
SPECIFIC GRAVITY: 1.03
DENSITY: 8.6 pounds per gallon
SAFETY (slip resistance): Exceeds requirements (A.S.T.M. Test D-2047)
PACKAGE SIZES: 4 x 1 gallon jugs
..... 5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
..... 55 gallon drums

rev. 09/12/18

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.