

SURTEC[®], Inc. *Surface Technology*

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

DURASHINE

FP-542

OUTSTANDING GLOSS & DURABILITY ULTRA HIGH SPEED BUFFABLE FLOOR POLISH

DESCRIPTION:

DURASHINE combines exceptional leveling and ease-of-use with superior burnishability. Outstanding floor protection and appearance can be achieved with less time and effort than ever before, resulting in significant labor savings. DURASHINE utilizes the latest polymer technology to create a product that combines the ultimate in durability, gloss and safety.

STRIPPING - If stripping is necessary, use SURTEC L.O.S or SUPER STRIP according to label directions.

APPLICATION - Use standard application procedures with a good quality rayon or synthetic blend string mop, or flat pad microfiber, applying thin to medium coats of DURASHINE.

ROUTINE MAINTENANCE - Use SURTEC's LF-150 or FLOOR SHINE High Speed Floor Maintainer at 1 or 2 oz. per gallon of water for damp mopping or scrubbing prior to high-speed buffing. Routine use of FLOOR SHINE with high speed buffing will increase the safety and durability of the floor polish, extending the time between recoats. High speed buffing DURASHINE will prolong the life of the polish and increase safety and durability, as well as increase shine and appearance. A propane buffer equipped with THERMAL GLOSS pads will achieve optimum buffing results, but any good quality high speed (1000+ rpm) buffer will achieve excellent results.

RESTORATION - Scrub the floor with a low speed buffer or automatic scrubber and red (light cleaning) pads using HC-150 or LF-150 Heavy Duty Cleaners at a dilution of 1 to 2 oz. per gallon of water to achieve a clean surface. Let dry, then apply a solution 1 part FLOOR SHINE diluted with 4 parts water in a manner similar to applying floor polish. Upon drying, high speed buff for optimum results.

RECOAT - Scrub the floor with a low speed buffer or automatic scrubber and blue or green (medium scrub) pads using HC-150 or LF-150 Heavy Duty Cleaners at a dilution of 2 to 4 oz. per gallon of water to achieve a clean surface. Rinse the floor with clean water and let dry, then apply one or more coats of DURASHINE, allowing each coat to dry before applying subsequent coats. Upon drying, high speed buff the last coat applied for optimum results.

SPECIFICATIONS:

| | |
|---------------------------------|--|
| COLOR: | White, stable emulsion |
| ODOR: | Mild, sweet |
| pH: | 8.6 ± 0.3 |
| HMIS RATING | Health =1 Flammability = 0 Physical Hazard = 0 |
| DENSITY | 8.7 lbs/gal |
| SPECIFIC GRAVITY | 1.05 |
| REFRACTOMETER SOLIDS: | 26.5% |
| FLASH POINT: | None (C.O.C. Method) |
| COVERAGE: | 2000 sq. ft. per gallon (average coverage on sealed floor) |
| DRYING TIME: | 30 minutes at 20°C. (68°F.), 50% relative humidity. |
| GLOSS: | 104 (A.S.T.M. Test D-523, 60°) |
| SAFETY (slip resistance): | Exceeds requirements (A.S.T.M. Test D-2047) |
| PACKAGE SIZES: | 4 x 1 gallon jugs |
| | 5 gallon Twin Pack (2 x 2.5 gal. bottles/box) |
| | 55 gallon drums |

rev. 09/12/18

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.