

SURTEC[®], Inc. *Surface Technology*

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

SURTEC[®] "CERTIFIED" GREEN L.O.S.

ST-935

LOW ODOR FLOOR POLISH STRIPPER CONCENTRATE

DESCRIPTION:

L.O.S. is a balanced, low odor, non-butyl formula designed for fast, complete removal of polymeric floor finishes. L.O.S. is ideal for removal of finishes in sites where the low odor is desired, for example, health care facilities. L.O.S. provides low foaming and easy rinsing. When used according to directions, L.O.S. is safe to use on vinyl composition tile, terrazzo, concrete and masonry surfaces. Do not use on cork or wood. If in doubt, consult SURTEC or pre-test in an inconspicuous area. L.O.S. is a concentrated stripper and is not intended to be used as a general purpose cleaner. At appropriate use dilution, L.O.S. meets CA Consumer Product VOC limits for "Floor Wax Strippers".

DIRECTIONS:

Dilute with up to 8 parts water for stripping light to medium buildup of floor polishes. Dilute with 4 parts water for heavy buildup. Allow solution to dissolve and raise old polish for 5 to 10 minutes before scrubbing. Let L.O.S. DO THE WORK FOR YOU. After scrubbing and pick up, rinse the floor and allow to dry. L.O.S.'s efficiency allows for fast and complete stripping without the need for aggressive scrubbing.

SPECIFICATIONS:

COLOR: Slightly turbid
ODOR: Mild
pH: 11.5 (concentrate)
..... 11.0 ± 0.1 (1:8 dilution)
HMIS RATING Health =2 Flammability = 0 Physical Hazard = 0
FLASH POINT: None (C.O.C. Method)
DILUTION USE RANGE: 1:4 to 1: 8
VOC CONTENT 21.4%(concentrate)
..... 2.4% (1:8 dilution for light to medium buildup)
..... 4.3% (1:4 dilution for heavy buildup)
DETERGENT TYPE: Nonionic
SPECIFIC GRAVITY: 1.01
DENSITY: 8.4 pounds per gallon
SOLUBILITY IN WATER: 100% (hard, soft and/or deionized water)
SHELF LIFE: Minimum 1 year from date of sale
PACKAGE SIZES: 4 x 1 gallon jugs
..... 5 gallon Twin Pack (2 x 2.5 gal. bottles/box)

THE GREEN SYSTEM BY SURTEC[®]

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.