

LF-150
LF-150
**LOW FOAM HEAVY DUTY CLEANER CONCENTRATE
 FOR AUTOMATIC SCRUBBERS**

DESCRIPTION:

LF-150 is a low-foaming version of SURTEC HC-150, a heavy duty, water base cleaning concentrate. It may be diluted to accomplish many specific cleaning requirements, especially in automatic floor scrubbers or other equipment where foam control is required. LF-150 is specifically formulated to deliver all of the cleaning power of HC-150, without excessive foaming. Because of its built-in water softeners, LF-150 mixes quickly in hot or cold, hard or soft water. At proper dilution ratios, LF-150 is safe to use on any surface not harmed by water, such as aluminum, plexiglas, painted surfaces, tile and terrazzo floors, etc. Consult SURTEC for specific recommendations.

DIRECTIONS:

For floor cleaning, fixtures and wall washing, dilute one part LF-150 with up to 128 parts water. To prepare a floor for recoating floor finish, scrub the floor twice with a low speed floor machine or automatic scrubber and blue or green (medium scrub) pads using LF-150 at a dilution of 2 to 4 oz. per gallon of water. Rinse the floor with clean water and let dry before applying floor finish. For wax stripping, steam cleaning, and general degreasing, dilute one part LF-150 with 10 parts water.

SPECIFICATIONS:

COLOR:	Green
COLOR:	Pine
pH:	11.5 ± 0.2 (concentrate)
.....	9.9 ± 0.2 (1:64 dilution with water)
.....	9.8 ± 0.2 (1:128 dilution with water)
HMIS RATING:	Health =1 Flammability = 0 Physical Hazard = 0
SURFACE TENSION:	29 dynes per cm. (at 2 oz. per gallon dilution)
V.O.C. CONTENT:	<0.1% by weight (at routine use concentration 1:64)
FLASH POINT:	None (C.O.C. Method)
DILUTION USE RANGE:	1:10 to 1:128
U.S.D.A. REGISTERED:	Yes
DETERGENT TYPES:	Nonionic/anionic
BIODEGRADABLE:	Yes
SPECIFIC GRAVITY:	1.04
DENSITY:.....	8.68 pounds per gallon
SOLUBILITY IN WATER:	100% (hard, soft and/or deionized water)
DETERGENT TYPES:	Nonionic/anionic
SHELF LIFE:	Minimum 1 year from date of sale
FREEZE/THAW STABILITY:	Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES:	4 x 1 gallon jugs
.....	5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
.....	55 gallon drums

rev. 05/06/22

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.