

SURTEC[®], Inc. *Surface Technology*

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

TRUE COLOR[™] STRIPPER

RT-201

STRIPPER / DESTAINER SYSTEM FOR RUBBER TILE FLOORS

DESCRIPTION:

The TRUE COLOR System is a two-part stripping system specially formulated to simultaneously strip and destain rubber tile flooring. The formula contains a stripper component (TRUE COLOR STRIPPER) and a stain removing component (TRUE COLOR ACTIVATOR), which are combined with water to form a solution which safely removes old floor finish and seal without discoloration (yellowing) of the rubber tile. Previous methods using chlorine bleach to remove discoloration can be discarded, as the TRUE COLOR System contains no chlorine bleach, which has produced many environmental and health concerns.

The TRUE COLOR System can be used safely for rubber tile, as well as other resilient tile flooring, including vinyl, composition vinyl, asphalt or linoleum. Masonry, concrete and stone tile can also be safely treated with the TRUE COLOR System. Always test a small area prior to application; if in doubt, consult SURTEC.

MIXING DIRECTIONS (each container of TRUE COLOR ACTIVATOR has a 12 ounce measuring cup or one ounce scoop included in the container):

For HEAVY BUILDUP: for each gallon of water, add 3.5 ounces of TRUE COLOR ACTIVATOR (RT-202) and mix until dissolved. Then to each gallon of ACTIVATOR and water solution, add 18 ounces of TRUE COLOR STRIPPER (RT-201).

For NORMAL STRIPPING: for each gallon of water, add 3.25 ounces of TRUE COLOR ACTIVATOR (RT-202) and mix until dissolved. Then to each gallon of ACTIVATOR and water solution, add 11 ounces of TRUE COLOR STRIPPER (RT-201) and stir until completely mixed.

USE DIRECTIONS:

Apply solution to floor, keeping the area wet for a minimum of twenty minutes. Scrub with a floor machine and strip pads or brushes. Vacuum up used solution, then rinse twice with copious amounts of clean, cold water. Allow to dry, then high speed buff, dust mop, and apply 2 coats of SURTEC FS-600 and 3 coats of ULTRA II, allowing each coat to dry before applying subsequent coats. High speed buff each coat for optimum results.

SPECIFICATIONS (RT-201 STRIPPER COMPONENT):

COLOR: Clear yellow

ODOR: Citrus

pH: 14.0 (concentrate)

..... 12.5 ± 0.2 (1:10 dilution)

HMIS RATING Health = 2 Flammability = 0 Physical Hazard = 0

FLASH POINT: None (C.O.C. Method)

DILUTION USE RANGE: 1:6 to 1:15

DETERGENT TYPE: Nonionic

SPECIFIC GRAVITY: 1.01

DENSITY: 8.4 pounds per gallon

SOLUBILITY IN WATER: 100% (hard, soft and/or deionized water)

SHELF LIFE: Minimum 1 year from date of sale

FREEZE/THAW STABILITY: Minimum 3 cycles (A.S.T.M. Test D-3209-82)

PACKAGE SIZES: 4 x 1 gallon jugs

..... 5 gallon Twin Pack (2 x 2.5 gal. bottles/box)

..... 55 gallon drums

rev. 3/7/03

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.