

FINAL STRIP
 ST-246
**EXTRA HEAVY DUTY
 FLOOR SEALER AND FINISH STRIPPER
 SUPER CONCENTRATE**

DESCRIPTION:

FINAL STRIP is a highly concentrated, low odor stripping solution designed for complete removal of extra heavy duty and high-build, difficult to remove waterborne floor finishes. When used according to directions, FINAL STRIP is safe to use on vinyl composition tile, terrazzo, concrete and masonry surfaces. Do not use on cork or wood. If in doubt, consult SURTEC or pre-test in an inconspicuous area. FINAL STRIP is a concentrated stripper and is not intended to be used as a general purpose cleaner.

DIRECTIONS:

Note: High performance, heavy-duty, cross-linked urethane floor finishes may require an hour or more dwell time for complete removal. Roughing the surface prior to stripping by scrubbing with a dilute solution of FINAL STRIP (4 oz. per gallon of water) and black stripping pads, high production pads, or aluminum oxide surface preparation pads may aid performance.

In most cases, dilute one part FINAL STRIP with 4 parts water. Apply solution to the floor and, to ensure proper wetting, scrub with black or high production stripping pads. Allow 15 minutes of dwell time and scrub again, applying more stripper, if necessary. Repeat the dwell time and scrubbing as necessary until removal is complete. Pick up stripping solution, rinse the floor and allow to dry.

SPECIFICATIONS:

COLOR:.....	Amber
ODOR:	Mild
pH:	14.0 (concentrate)
.....	13.3 ± 0.2 (1:4 dilution)
HMIS RATING :	Health = 3 Flammability = 0 Physical Hazard = 0
FLASH POINT:	> 200°F (C.O.C. Method)
DILUTION USE RANGE:	1:4 to 1:20
VOC CONTENT:	Less than 2% by weight at 1:8 dilution for Light/Medium Duty Stripping
.....	Less than 4% by weight at 1:4 dilution for Heavy Duty Stripping
DETERGENT TYPE:	Nonionic
SPECIFIC GRAVITY:	1.09
DENSITY:	9.0 pounds per gallon
SOLUBILITY IN WATER:	100% (hard, soft and/or deionized water)
SHELF LIFE:	Minimum 1 year from date of sale
PACKAGE SIZES:	4 x 1 gallon jugs
.....	5 gallon pails