

# FOAMING DEGREASER

GC-276

## HEAVY DUTY GREASY SOIL CLEANER CONCENTRATE GRILL, HOOD AND OVEN CLEANER

**DESCRIPTION:**

FOAMING DEGREASER is the product of choice for cleaning greasy concrete, quarry tile, or ceramic tile floors in butcher areas, bakeries, deli's, or any greasy area of a kitchen or food processing area. FOAMING DEGREASER is formulated to quickly dissolve and emulsify baked-on greasy soils from grills, ovens, racks, deep fat fryers, ventilator hoods, etc. FOAMING DEGREASER is authorized by U.S.D.A. for use in federally inspected meat and poultry plants.

**DIRECTIONS:**

FLOORS, WALLS, TABLES, COUNTERS: Use FOAMING DEGREASER for cleaning concrete and quarry or ceramic tile floors and surfaces in food preparation or processing areas at a dilution of 1 to 12 ozs. per gallon of water, depending on the level of soiling. Rinse with clean water or properly diluted SURTEC NO RINSE SANITIZER.

OVENS, HOODS, GRILLS: Dilute with an equal part of water and apply to ovens and grills at temperatures up to 180° F. Neutralize surfaces with vinegar after cleaning. Rinse with clean water. Caution: FOAMING DEGREASER contains strong alkaline detergents and must be used with protection for skin and eyes.

**SPECIFICATIONS:**

COLOR: .....	Clear, light straw
ODOR: .....	Mild
pH: .....	13.6 ± 0.2 (concentrate)
.....	13.0 ± 0.2 (10% dilution with water)
.....	12.2 ± 0.2 (1% dilution with water)
HMIS RATING: .....	Health = 3 Flammability = 0 Physical Hazard = 1
FLASH POINT: .....	None (C.O.C. Method)
SURFACE TENSION: .....	29 dynes per cm. (at 1% dilution)
V.O.C. CONTENT: .....	Less than 0.1% by weight (concentrate)
DILUTION USE RANGE: .....	1:128 to undiluted
U.S.D.A. REGISTERED: .....	Yes
DETERGENT TYPE:.....	Nonionic/Anionic
BIODEGRADABLE:.....	Yes
SPECIFIC GRAVITY: .....	1.07
DENSITY: .....	8.9 pounds per gallon
SOLUBILITY IN WATER:.....	100% (hard, soft and/or deionized water)
SHELF LIFE: .....	Minimum 1 year from date of sale
FREEZE/THAW STABILITY: .....	Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES: .....	4 x 1 gallon jugs
.....	5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
.....	55 gallon drums

rev. 01/19/21

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.