

GRAFFITI BUSTER VOC
 GB-290
INK & SPRAY PAINT REMOVER

DESCRIPTION:

GRAFFITI BUSTER VOC was developed specifically to remove all types of graffiti material from various surfaces. GRAFFITI BUSTER VOC is extremely effective in the removal of ink, spray paint, lipstick, felt marking pens, etc., from surfaces such as formica, vinyl, baked enamel painted surfaces, cement, brick, marble, and granite. Be sure to test surface in an inconspicuous area to preclude surface damage. GRAFFITI BUSTER VOC will totally remove most graffiti materials from nonporous surfaces. Porous surfaces should be precoated with SURTEC's GRAFFITI BARRIER VOC or SURTEC SURPRO 100LV for the most efficient graffiti removal process. GRAFFITI BUSTER VOC meets CA Air Resources Board regulations at less than 30% VOC by weight.

DIRECTIONS:

Pre-test all surfaces in an inconspicuous area to be sure that they are not affected by GRAFFITI BUSTER VOC. GRAFFITI BUSTER VOC is ready to use; do not dilute. Spray or brush GRAFFITI BUSTER VOC on the surface containing graffiti. Allow GRAFFITI BUSTER VOC to work from 1 to 10 minutes depending on the type of graffiti to be removed. Many types of graffiti can be wiped off immediately upon application, for example counter tops, restroom partitions, etc. For large, hard to clean surfaces, apply GRAFFITI BUSTER VOC, allow time for graffiti to dissolve and wash off with a pressure washer using HC-150 at 2 ounces per gallon of water. Collect rinse solution and dispose of according to local, state and federal regulations.

SPECIFICATIONS:

COLOR:	Clear, amber
ODOR:	Aromatic solvent
COVERAGE:.....	200 to 400 square feet per gallon (average; actual cover coverage depends on porosity of surface, amount and type of graffiti)
FLASH POINT:	142° F. (C.O.C. Method)
pH:	12.8 ± 0.5
HMIS RATING:	Health = 2 Flammability = 2 Physical Hazard = 0
% ACTIVE INGREDIENTS:	Greater than 90%
SPECIFIC GRAVITY:	0.98
DENSITY:	8.12 pounds per gallon
SAFE FOR USE ON:	Concrete, brick, stucco and similar masonry surfaces; Formica; baked enamel painted surfaces
V.O.C. CONTENT:	29.4% by weight
PACKAGE SIZES:.....	6 x 1 gallon cans per case
	5 gallon pails
	55 gallon drums

 **WARNING:** This product can expose you to chemicals including cumene which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

rev. 01/19/21
 SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.