

AF-410
AF-410
DEFOAMER SUPER CONCENTRATE

DESCRIPTION:

AF-410 is a highly concentrated defoaming agent. Its uses include defoaming of recovery tanks in automatic floor scrubbers and carpet soil extraction equipment. AF-410 can be used in any equipment where excessive foam is a problem.

DIRECTIONS:

SHAKE WELL BEFORE USING. In automatic floor scrubbers, use between 1/2 oz. and 2 oz. per 5 gallons of tank capacity, depending on severity of foam. In carpet soil extraction equipment, use 1 oz. per 5 gallons of recovery tank capacity.

Consult SURTEC for other uses and appropriate dilution rates.

SPECIFICATIONS:

COLOR: Milk white, opaque
ODOR: None
pH: 7.5 ± 0.5 (concentrate)
FLASH POINT: None (C.O.C. Method)
DILUTION USE: 1:640 (1 ounce per 5 gallons)
SPECIFIC GRAVITY: 1.0
DENSITY: 8.34 pounds per gallon
SOLUBILITY IN WATER: 100% (hard, soft and/or deionized water)
SHELF LIFE: Minimum 1 year
FREEZE/THAW STABILITY: Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES: 4 x 1 gallon jugs

rev. 3/7/03

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.