

ENDURE

FP-522

LONG LASTING LOW MAINTENANCE EXTRA DURABLE FLOOR FINISH

DESCRIPTION:

ENDURE floor finish is designed to provide extreme durability under high traffic conditions. ENDURE provides a rich, long-lasting gloss, and a hard, non-yellowing film which resists soiling and black marking. ENDURE is the product of choice for high use, low maintenance floors in demanding environments such as restaurants and convenience stores. ENDURE exceeds the Coefficient of Friction safety standards of ASTM Designation D-2047.

APPLICATION - Use standard application procedures with a good quality rayon or synthetic blend string mop, or flat pad microfiber, applying thin to medium coats of ENDURE. Allow 30 minutes of dry time between coats or before opening to traffic. Three or more coats in one application period are possible with ENDURE. Note: On a bare, stripped floor, four or more coats may be required to achieve the highest level of gloss.

ROUTINE MAINTENANCE - Use SURTEC HC-150 or LF-150 Heavy Duty Cleaners at 1 or 2 ozs. per gallon of water for routine maintenance by damp mopping or scrubbing. Occasional high speed buffing of ENDURE will prolong the life of the polish and increase safety and durability, as well as increase shine and appearance. A propane buffer equipped with natural hog hair pads will achieve excellent buffing results, but any good quality high speed (1000+ rpm) buffer will achieve suitable results.

RECOAT - Scrub the floor with a low speed buffer or automatic scrubber and blue or green (medium scrub) pads using HC-150 or LF-150 Heavy Duty Cleaners at a dilution of 2 to 4 ozs. per gallon of water to achieve a clean surface. Rinse the floor with clean water and let dry, then apply one or more coats of ENDURE, allowing each coat to dry before applying subsequent coats.

STRIPPING - If stripping is necessary, use SURTEC L.O.S. or SUPER STRIP according to label directions.

SPECIFICATIONS:

COLOR:	Milky white, stable emulsion, dries clear
ODOR:	Sweet
pH:	8.2 ± 0.1
SPECIFIC GRAVITY/DENSITY:	1.07 / 8.9 pounds per gallon
FLASH POINT:	None (C.O.C. Method)
VOC CONTENT:	Less than 1% by weight
HMIS RATING:	Health = 1 Flammability = 0 Physical Hazard = 0
REFRACTOMETER SOLIDS:	22%
GLOSS:	92 (A.S.T.M. Test D-523, 60°)
DRYING TIME:	30 minutes at 20°C. (68°F.), 50% relative humidity
COVERAGE:	2000 sq. ft. per gallon (average coverage on a sealed floor)
LEVELING:	Excellent (A.S.T.M. Test D-2801)
POWDERING RESISTANCE:	Excellent (A.S.T.M. Test D-2048-82)
RECOATABILITY:	Excellent (A.S.T.M. Test D-3153-78)
SAFETY (slip resistance):	Exceeds requirements (A.S.T.M. Test D-2047)
PACKAGE SIZES:	4 x 1 gallon jugs
.....	5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
.....	55 gallon drums

 **WARNING:** This product can expose you to chemicals including ethylene glycol (ingested), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

rev. 01/19/21

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.