

NATURAL BEAUTY

FP-527

LOW GLOSS FINISH & SEALER FOR INTERIOR TILE, TERRAZZO, MARBLE AND GRANITE

DESCRIPTION:

NATURAL BEAUTY was developed to answer the architectural need for a natural looking, low gloss finish for stone that will provide safety and surface protection. NATURAL BEAUTY combines the ease of use and maintenance of standard waterborne floor finishes with a chemical technology which produces a low gloss, no matter how many coats are applied.

NATURAL BEAUTY is safe for use on interior marble, granite (including polished and flame-cut), porous stone tile, terrazzo and similar masonry surfaces. NATURAL BEAUTY is also recommended for vinyl composition tile and pure vinyl flooring. Do not use on cork or unsealed wood.

NATURAL BEAUTY exceeds the Co-efficient of Friction safety standards of ASTM Designation D-2047.

APPLICATION:

Old finishes, sealers and dirt should be removed prior to application. Use SURTEC L.O.S., SUPER STRIP or ULTRA STRIP for fast, efficient stripping of old floor finishes. Rinse thoroughly with clean water and allow to dry. Use standard application procedures and a clean wax mop or microfiber applicator to apply 2 to 4 thin to medium coats of NATURAL BEAUTY. Make sure each coat is completely dry before applying subsequent coat or opening to traffic. NATURAL BEAUTY requires no sealer; however, if a sealer is desired, SURTEC CL-631, BOND COAT or FS-600 may be used.

MAINTENANCE:

Use SURTEC HC-150 or LF-150 at a dilution of 1 to 2 ounces per gallon of water for routine wet mopping or scrubbing. To remove surface scuffs or mars, machine buff using a buffing pad or brush. Buffing may slightly increase the gloss of NATURAL BEAUTY, but will harden the surface and prolong the life of the finish.

SPECIFICATIONS:

COLOR:	Milk white, dries clear
ODOR:	Sweet
pH:	8.1 ± 0.2
SPECIFIC GRAVITY/DENSITY:	1.05 / 8.8 pounds per gallon
FLASH POINT:	None (C.O.C. Method)
VOC CONTENT:	Less than 1% by weight
HMIS RATING:	Health = 1 Flammability = 0 Physical Hazard = 0
REFRACTOMETER SOLIDS:	19%
GLOSS:	76 (A.S.T.M. Test D-523, 60°)
DRYING TIME:	30 minutes at 20°C. (68°F.), 50% relative humidity
COVERAGE:	
FIRST COAT (bare floor):.....	800 to 1200 square feet per gallon
SECOND (or more) COAT.....	1500 to 2000 square feet per gallon
LEVELING:	Excellent (A.S.T.M. Test D-2801)
POWDERING RESISTANCE:	Excellent (A.S.T.M. Test D-2048-82)
RECOATABILITY:	Excellent (A.S.T.M. Test D-3153-78)
SAFETY (slip resistance):	Exceeds requirements (A.S.T.M. Test D-2047)
PACKAGE SIZES:	4 x 1 gallon jugs
.....	5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
.....	55 gallon drums

rev. 01/19/21

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.