

FP-575
FP-575
**HEAVY DUTY HIGH SOLIDS
 METAL INTERLOCK FLOOR POLISH**

DESCRIPTION:

FP-575 is a high solids floor polish designed to achieve maximum gloss quickly and maintain it for extra-long periods of time. Each coat provides a clear, durable film for the protection of floor surfaces. The high solids, metal interlock system allows a floor to achieve beauty and protection rapidly without seal, thereby providing a savings in labor and material. FP-575 is the product of choice for heavy foot traffic, low maintenance environments such as airports, transit stations, restaurants and convenience stores. FP-575 exceeds the Coefficient of Friction safety standards of ASTM Designation D-2047.

DIRECTIONS:

APPLICATION - Use standard application procedures with a good quality rayon or synthetic blend string mop, or flat pad microfiber, applying thin to medium coats of FP-575. Allow 30 minutes of dry time between coats or before opening to traffic. Three or more coats in one application period are possible with FP-575 and, on a bare, stripped floor, may be required to achieve the highest level of gloss.

ROUTINE MAINTENANCE - Use SURTEC HC-150 or LF-150 Heavy Duty Cleaners at 1 or 2 ozs. per gallon of water for routine maintenance by damp mopping or scrubbing. Occasional high speed buffing of FP-575 will prolong the life of the polish and increase safety and durability, as well as increase shine and appearance. A propane buffer equipped with natural hog hair pads will achieve excellent buffing results, but any good quality high speed (1000+ rpm) buffer will achieve suitable results.

RECOAT - Scrub the floor with a low speed buffer or automatic scrubber and blue or green (medium scrub) pads using HC-150 or LF-150 Heavy Duty Cleaners at a dilution of 2 to 4 ozs. per gallon of water to achieve a clean surface. Rinse the floor with clean water and let dry, then apply one or more coats of FP-575, allowing each coat to dry before applying subsequent coats. Upon drying, the last coat may be high speed buffed if desired.

STRIPPING - If stripping is necessary, use SURTEC L.O.S. or SUPER STRIP according to label directions.

SPECIFICATIONS:

COLOR:	Milk-white, stable emulsion, dries clear
ODOR:	Sweet
pH:	8.1 ± 0.2
SPECIFIC GRAVITY/DENSITY:	1.04 / 8.7 pounds per gallon
FLASH POINT:	None (C.O.C. Method)
VOC CONTENT:	Less than 1% by weight
HMS RATING:	Health = 1 Flammability = 0 Physical Hazard = 0
REFRACTOMETER SOLIDS:	27%
GLOSS:	93 (A.S.T.M. Test D-523, 60°)
DRYING TIME:	30 minutes at 20°C. (68°F.), 50% relative humidity
COVERAGE:	2000 sq. ft. per gallon (average coverage on a sealed floor)
LEVELING:	Excellent (A.S.T.M. Test D-2801)
POWDERING RESISTANCE:	Excellent (A.S.T.M. Test D-2048-82)
RECOATABILITY:	Excellent (A.S.T.M. Test D-3153-78)
SAFETY (slip resistance):	Exceeds requirements (A.S.T.M. Test D-2047)
PACKAGE SIZES:	4 x 1 gallon jugs
.....	5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
.....	55 gallon drums

 **WARNING:** This product can expose you to chemicals including ethylene glycol (ingested), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

rev. 01/19/21

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.