

SAFETY DATA SHEET

| | | |
|---|-----------------------------|----------------------------------|
| FINAL COAT MATTE (PARTS A AND B MIXED) | <i>SDS Number: FP-596AB</i> | <i>Revision Date: 10/15/2019</i> |
|---|-----------------------------|----------------------------------|




1. PRODUCT AND COMPANY IDENTIFICATION:
Product Name: FINAL COAT MATTE
Product Code: FP-596
Product Use: Institutional Floor Polish
Synonyms: Proprietary Waterborne Floor Polish
Chemical Formula: Mixture of substances listed below with nonhazardous additions
Restrictions: Institutional, Commercial, Retail and Industrial Floor Care Use Only

Manufacturer: Surtec, Inc.
 1880 N. MacArthur Dr
 Tracy, CA 95376
 209.820.3700
 Toll Free 800.877.6330

Emergency contact: Chemtrec 800.424.9300
 CCN No. 21541

2. HAZARD IDENTIFICATION:

GHS CLASSIFICATION:

| <u>HEALTH</u> | <u>ENVIRONMENTAL</u> | <u>PHYSICAL</u> |
|--|--|-----------------|
| <i>Skin Sensitization: Category 1</i> | <i>Acute Toxicity: None Known Chronic Toxicity: None Known</i> | <i>None</i> |
| <u>GHS Pictogram</u>  | <u>Signal Word:</u> <i>Warning</i> | |
| <u>Hazard Statements</u> May cause mild skin and eye irritation May cause an allergic skin reaction | | |
| <u>Precautionary Statements</u> Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mists, vapors or spray. IF IN EYES: Rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation occurs and persists, get medical attention. IF ON SKIN: Wash with soap and water. If irritation occurs and persists, get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Severe asthmatic reactions can occur in sensitized individuals. Asthmatic symptoms may have a delayed onset. Get medical attention if you feel unwell. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison center. Store in a closed container. Dispose of contents/container in accordance with local regulation. | | |

SAFETY DATA SHEET

**FINAL COAT MATTE
(PARTS A AND B MIXED)**

SDS Number: FP-596AB

Revision Date: 10/15/2019

3. COMPOSITION/INFORMATION ON INGREDIENTS:

| INGREDIENT | CAS NO. | PERCENT | HAZARDOUS |
|---|--------------|----------|-----------|
| ALIPHATIC POLYISOCYANATE BASED ON HEXAMETHYLENE DIISOCYANATE | TRADE SECRET | 3-5% | YES |
| DIPROPYLENE GLYCOL MONOMETHYL ETHER | 34590-94-8 | 0.1-0.5% | YES |
| TRIETHANOLAMINE | 121-44-8 | 0.1-0.5% | YES |
| HEXAMETHYLENE-1,6-DIISOCYANATE | 822-06-0 | <0.1% | YES |
| DIPROPYLENE GLYCOL METHYL ETHER ACETATE | 88917-22-0 | 0.1-1% | YES |
| Exact Percentages are being withheld as trade secret information. | | | |

4. FIRST-AID MEASURES:

Eye Contact: Rinse with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation occurs and persists, get medical attention.

Skin Contact: Wash with soap and water. If irritation occurs and persists, get medical attention.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Severe asthmatic reactions can occur in sensitized individuals. Asthmatic symptoms may have a delayed onset. Get medical attention if you feel unwell.

Ingestion: Rinse mouth. Do NOT induce vomiting. Get medical attention if you feel unwell.

5. FIRE-FIGHTING MEASURES:

Fire Extinguishing media: Use water spray dry chemical, carbon dioxide or regular foam. Move containers away from fire area if can be done without risk.

Hazards during fire-fighting:

Containers may rupture when exposed to extreme heat. Isocyanate and diisocyanate vapors, and other toxic gases may be generated by thermal decomposition.

Protective equipment for fire-fighting:

Wear NFPA-approved self-contained breathing apparatus, helmet, hood, boots and gloves.

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions:

Use recommended personal protective clothing and equipment. To prevent slipping, do not walk through spilled material.

Environmental precautions:

Follow all Federal, State and Local regulations when storing and disposing of substances. Do not allow material to run off of work area, and material should be absorbed, collected and disposed of in accordance with regulations. Keep product from entering storm drains. Consult local and federal guidelines for proper disposal of these materials.

Cleanup:

- For small amounts of released material: Mop or vacuum up then transfer to suitable container for disposal. - For large

amounts of released material: Dike around spilled material with absorbent to contain. Spilled material may be mopped or vacuumed up, then transferred to plastic containers for disposal.

SAFETY DATA SHEET

| | | |
|---|-----------------------------|----------------------------------|
| FINAL COAT MATTE (PARTS A AND B MIXED) | SDS Number: FP-596AB | Revision Date: 10/15/2019 |
|---|-----------------------------|----------------------------------|

7. HANDLING and STORAGE:

Handling:

General advice - No specific measures are necessary provided product and recommended protective clothing/equipment are used correctly. Do not mix with other chemicals. This is a commercial product, not intended for home use. Keep out of reach of children.

Storage:

General advice - Protect against physical damage. Store unmixed product in tightly closed containers in a cool, well ventilated area. Do not allow product to freeze. When mixed, this product has a useable work time (pot life) of 8 hours. Do not attempt to store mixed material. Dispose of unused material according to local regulations.

Shelf Life:

12 months

8. EXPOSURE CONTROLS and PERSONAL PROTECTION:

Advice on system design:

Provide local exhaust ventilation to control vapors for published exposure limits.

Personal protective equipment (HMIS rating 'B'):

Eye protection: Wear safety glasses with side shields or safety goggles to prevent exposure or full face shield if splash hazard exists.

Skin protection: Chemical-resistant gloves. Wear appropriate protective clothing to prevent possible skin contact.

Respiratory protection: Product is not intended for airless or other paint spray application. Do not breathe mists, vapors or spray. Use proper NIOSH-OSHA respirator fitted with proper cartridges if mists are generated, ventilation is inadequate or exposure limits are exceeded.

General safety and hygiene measures: Exercise stringent hygiene practices to minimize exposure.

If contact occurs, wash any body part with soap and water immediately. Wash hands after use, and before eating, drinking or smoking.

Other protective measures:

Nearby running water on the job site is necessary, should an accident occur.

Exposure Guidelines:

ACGIH TLV: 100 ppm (34590-94-8), 1 ppm (121-44-8), 0.005 ppm (Aliphatic Polyisocyanate and 822-06-0)

STEL: 150 ppm (34590-94-8), 3 ppm (121-44-8)

OSHA PEL: 100 ppm (34590-94-8), 25 ppm (121-44-8)

9. PHYSICAL and CHEMICAL PROPERTIES:

| | | | |
|-----------------------------|---|----------------------------------|--------------------------|
| Appearance: | White Liquid | Flash Point: | > 200°F |
| Odor: | Sweet | Upper/Lower Flammability Limits: | No information available |
| pH value: | 8.1 +/- 0.2 | Relative Density (water): | 1.03 |
| Specific gravity: | 1.03 (H2O = 1) | Auto-Ignition Temperature: | No information available |
| Solidification temperature: | No information available | Decomposition temperature: | No information available |
| Freezing/Melting point: | 32 °F (0 °C) | Partition Coefficient | No information available |
| Boiling point: | 212°F (100 °C) | Odor Threshold | No information available |
| Vapor density: | No information available | Viscosity: | < 10 cps. |
| Vapor pressure: | No information available | Partition Coefficient | No information available |
| Evaporation Rate: | No information available | Solubility in water: | Miscible |
| Regulatory VOC: | <0. 5% by weight (as mixed with Part B) | | |

SAFETY DATA SHEET

**FINAL COAT MATTE
(PARTS A AND B MIXED)**

SDS Number: FP-596AB

Revision Date: 10/15/2019

10. STABILITY and REACTIVITY:

Conditions to avoid: Freezing. Excessive heat or flame.

Substances to avoid: Strong oxidizing agents, acids and bases.

Hazardous reactions: Product is chemically stable under normal conditions of use and storage.

Decomposition or By-products: In fire conditions: carbon monoxide (CO), carbon dioxide (CO₂) and nitric oxides (NO_x), hydrogen cyanide, isocyanate, isocyanic acid.

11. TOXICOLOGY INFORMATION:

Acute Toxicity (Symptoms):

Oral: Ingestion may cause nausea, vomiting, and diarrhea.

Eye irritation: Mild irritation, redness and tearing.

Skin irritation: Irritation, redness, itching and swelling. Can cause sensitization. Persons with allergic reaction may also experience rash.

Inhalation: Inhalation of vapors may cause irritation to the respiratory tract with runny nose, sore throat, coughing and difficulty breathing. **Sensitization:** Skin: Yes Respiratory: N/A

Chronic Toxicity:

Note: Although not classified as a respiratory sensitizer, repeated overexposures to vapors may cause sensitization in certain individuals to isocyanates. This sensitization may cause asthma or asthma-like symptoms even with low levels of later exposure to isocyanate. Symptoms include chest tightness, wheezing, cough, shortness of breath or asthmatic attack. Symptoms may be delayed onset.

Other information: No carcinogenic substances as defined by IARC, NTP and/or OSHA.

12. ECOLOGICAL INFORMATION:

Biodegradation:

Test method: Unspecified

Analysis method: Unspecified

Degree of elimination: Not readily biodegradable.

Environmental toxicity:

Acute and prolonged toxicity to fish: Not Established

Toxicity to microorganisms: Not Established

Other ecotoxicological advice: Not Established

13. DISPOSAL CONSIDERATIONS:

Waste disposal of substance: Dispose of in accordance with all Federal, State and Local regulations when storing and disposing of substances. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA (EPA regulations for hazardous waste).

Container disposal: Dispose of in a licensed facility in accordance with local regulations.

RCRA:

Unspecified.

SAFETY DATA SHEET

**FINAL COAT MATTE
(PARTS A AND B MIXED)**

SDS Number: FP-596AB

Revision Date: 10/15/2019

14. TRANSPORTATION INFORMATION:

Part A

DOT:

Proper Shipping Name: WAX, LIQUID (NON-HAZARDOUS)

Part B

DOT:

Proper Shipping Name: PAINT RELATED MATERIAL (NON-HAZARDOUS)

15. REGULATORY INFORMATION:

Federal Regulations:

Registration status:

TSCA, US:

All components are listed or exempt.

SARA hazard category (EPCRA 311/312): Acute health hazard

SARA TITLE III, SECTION 313:

CAS Number: _____ **Chemical Name:**

None

State Regulations:

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm

CAS Number: _____ **Chemical Name:**

None

CA Cleaning Product Right To Know Act of 2017: Ingredient Disclosure

| INGREDIENT | CAS NUMBER | FUNCTION |
|---|---------------|---------------------------------|
| WATER | 7732-18-5 | DILUENT |
| PROPRIETARY POLYMER DISPERSIONS | NOT AVAILABLE | POLYMER FILM-FORMER |
| ALIPHATIC POLYISOCYANATE BASED ON HEXAMETHYLENE DIISOCYANATE | NOT AVAILABLE | POLYMER CROSSLINKER |
| DIPROPYLENE GLYCOL MONOMETHYL ETHER | 34590-94-8 | COALESCING SOLVENT |
| DIPROPYLENE GLYCOL METHYL ETHER ACETATE | 88917-22-0 | SOLVENT DILUENT |
| TRIETHANOLAMINE | 121-44-8 | NEUTRALIZER |
| FLUORINATED ALCOHOL, REACTION PRODUCTS WITH PHOSPHOROUS OXIDE, AMMONIUM SALTS | NOT AVAILABLE | FLUOROSURFACTANT LEVELING AGENT |
| POLYDIMETHYLSILOXANE EMULSION | NOT AVAILABLE | DEFOAMER |
| HEXAMETHYLENE-1,6-DIISOCYANATE | 822-06-0 | NONFUNCTIONAL CONSTITUENT |

SAFETY DATA SHEET

**FINAL COAT MATTE
(PARTS A AND B MIXED)**

SDS Number: FP-596AB

Revision Date: 10/15/2019

16. OTHER INFORMATION:


NFPA Rating:

Health: 1 Fire: 0 Reactivity: 0 Special Hazard: none

HMIS III Rating:

Health: 1 Flammability: 0 Physical Hazard: 0
Personal Protection: B (safety glasses with side shields and chemical-resistant gloves)

Both NFPA and HMIS III rating systems use a numbering scale that ranges from 0 to 4 to indicate the degree of hazard. A value of zero means the substance possesses no hazard while a value of four indicates high hazard.



Prepared by: Surtec, Inc. 10/15/2019 **Revision No.:** Original

Local Contact Information:

Surtec, Inc.
209-820 3700; Toll Free 800-877-6330 (8 a.m. to 5 p.m., M-F, PST)
www.surtecsystem.com

Notice: The information provided is accurate to the best of our knowledge and is offered in good faith. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in specific context of the intended use and determine whether they are appropriate.

Warranty: This is a proprietary SURTEC product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over product use, no warranty is made as to the effects of such use (neither expressed nor implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact SURTEC with any questions regarding this policy.