

TILE BRITE X
 TB-801
EXTRA STRENGTH SCUM & SCALE REMOVER

DESCRIPTION:

TILE BRITE X is an extra strength formulation of SURTEC TILE BRITE. It is recommended for use on rust, scale, mineral or lime deposits where regular strength TILE BRITE has little or no effect. Etching of cement, grout and other masonry type surfaces will vary depending on the surface, conditions, and especially the dilution rate and dwell time. Always test an inconspicuous area prior to use; if in doubt, consult SURTEC.

DIRECTIONS:

TILE BRITE X may be used undiluted if proper pretesting confirms the need for using it full strength; most applications will require diluting with 2 to 10 parts water. Apply to surface with acid pump-up sprayer, trigger sprayer, damp rag or sponge. Adjust dwell time from 1 to 10 minutes depending on results desired. Neutralize using properly diluted SURTEC HC-150 or SC-210, followed by thorough rinsing with clean water.

SPECIFICATIONS:

COLOR:	Pink
ODOR:	Pine
DILUTION RATE:	1:10 to undiluted
METHOD OF APPLICATION:	Acid-proof pump-up or trigger sprayer
pH (Concentrate):	0.5 ± 0.2
HMIS RATING:	Health = 2 Flammability = 0 Physical Hazard = 0
DETERGENT TYPE:	Nonionic
SPECIFIC GRAVITY / DENSITY:	1.3 / 11.0 pounds per gallon
FLASH POINT:	None (C.O.C. Method)
SURFACE TENSION:	29 dynes per cm. (at 1:10 dilution)
V.O.C. CONTENT:	Less than 0.5% (Concentrate)
SOLUBILITY IN WATER:	100% (hard, soft and/or deionized water)
FREEZE/THAW STABILITY:	Minimum 3 cycles (A.S.T.M. Test D-3209-82)
SHELF LIFE:	Minimum 1 year from date of sale
CONTAINER SIZES AVAILABLE:.....	4 x 1 gallon jugs 5 gallon pail 55 gallon drum