

SURTEC, Inc. *Surface Technology*

1880 N MACARTHUR DR. TRACY, CA 95376 Phone (209) 820-3700 Fax (209) 820-3793

LIME SCALE REMOVER SR-805 **READY-TO-USE SCUM AND SCALE REMOVER**

DESCRIPTION:

LIME SCALE REMOVER is a new generation blend of organic acid, biodegradable detergents and corrosion inhibitors formulated for efficient removal of lime scale, mineral deposits and soap scum in a ready-to-use formula. The organic acid used in LIME SCALE REMOVAL is comparable to hydrochloric (muriatic) acid in its ability to dissolve calcium salts, but without the corrosivity, noxious vapor or white residue typically associated with acid-based scale removers. LIME SCALE REMOVER thoroughly penetrates and removes calcium deposits, soap scum and rust stains from bath tubs, fixtures, shower tile, drinking fountains, glass, and chrome. LIME SCALE REMOVER will not harm these surfaces when used as directed.

DIRECTIONS:

Pre-test in an inconspicuous area prior to use. Do not use on carpet, fabrics, mirrors or on any surface affected by acids, such as marble, limestone, or cementitious surfaces. After a thorough cleaning with a tile and grout cleaner, such as SURTEC OMNI CLEAN, LIME SCALE REMOVER may be used as a final treatment to mildly etch and "brighten" grout.

Apply LIME SCALE REMOVER to the surface with an acid proof pump-up sprayer, trigger sprayer, damp rag or sponge. Allow sufficient time for thorough penetration and reaction. Scrub as necessary and rinse thoroughly with clean water, or, if desired, neutralize using properly diluted SURTEC HC-150 or SC-210, followed by a clean water rinse.

SPECIFICATIONS:

COLOR:	Green
ODOR:	Wintergreen
DILUTION RATE:	Ready-To-Use
METHOD OF APPLICATION:	Acid-proof pump-up sprayer, rag or sponge
COVERAGE:	100 to 200 square feet per gallon
pH (Concentrate):	0.5 ± 0.2
HMIS RATING:	Health = 2 Flammability = 0 Physical Hazard = 0
DETERGENT TYPE:	Nonionic
SPECIFIC GRAVITY / DENSITY:	1.03 / 8.6 pounds per gallon
FLASH POINT:	None (C.O.C. Method)
V.O.C. CONTENT:	Less than 0.5%
SOLUBILITY IN WATER:	100% (hard, soft and/or deionized water)
SHELF LIFE:	Minimum 1 year from date of sale
CONTAINER SIZES AVAILABLE: ...	4 x 1 gallon jugs
.....	5 gallon pail
.....	55 gallon drum

rev. 01/11/21

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.