

SURTEC, Inc. *Surface Technology*

1880 N MACARTHUR DR. TRACY, CA 95376 Phone (209) 820-3700 Fax (209) 820-3793

SOY SOLVENT SS-843 **SAFETY SOLVENT** **ADHESIVE AND TIRE MARK REMOVER**

DESCRIPTION:

SOY SOLVENT was developed to provide a user-safe and environment-safe product to dissolve adhesives, tire marks, and other organic based materials previously cleanable only with petroleum based product. Formulated with naturally derived solvents, SOY SOLVENT is not flammable (flash point is 425° F.), has no dangerous vapors, evaporates slowly for adequate work time and is without the other problems associated with petroleum solvents. SOY SOLVENT may be used for any cleaning job on concrete, stone and masonry that requires good solvency, such as tile adhesive and hydrocarbon-based concrete curing agent removal, and removal of tire marks, graffiti inks, gums, and glues from concrete warehouse floors and walls. SOY SOLVENT is compliant with California Air Resources Board VOC limits for Adhesive and Graffiti Removers.

DIRECTIONS:

SOY SOLVENT is water dispersible, but will be most efficient when used undiluted. For adhesive, curing agent and heavy tire mark removal, apply to the area to be cleaned, allow sufficient dwell time for SOY SOLVENT to penetrate and dissolve the material and scrub the area to enhance removal. Wet vacuum dissolved material and follow with a thorough cleaning with a heavy duty cleaner/degreaser, such as SURTEC SC-210 diluted 2 -4 ounces per gallon with water. For spot cleaning spray marks, graffiti or oily soils, apply SOY SOLVENT, scrub and wipe with a cloth or a sponge dampened with water. SOY SOLVENT may be diluted with up to 10 parts water for cleaning sensitive surfaces (resilient tile, painted or plastic substrates). Always test an inconspicuous area or consult SURTEC prior to use.

SPECIFICATIONS:

COLOR:	Clear amber liquid
ODOR:	Mild, vegetable oil
DILUTION RATE:.....	Ready to use
METHOD OF APPLICATION:	Solvent proof pump-up sprayer, mop, brush
HMIS RATING:	Health = 1 Flammability = 1 Physical Hazard = 0
COVERAGE (estimated):	100 to 200 square feet per gallon
DWELL TIME:	5 to 20 minutes or more, depending on type and amount of substance (adhesive, tire mark, glue, etc.) to be removed.
BIODEGRADABLE:	Yes
DETERGENT TYPE:	Nonionic
SPECIFIC GRAVITY:	0.90 / 7.5 pounds per gallon
FLASH POINT:.....	425° F.
V.O.C. CONTENT:	Less than 5%
SOLUBILITY IN WATER:.....	Miscible
FREEZE/THAW STABILITY:	Protect from freezing
SHELF LIFE:.....	Minimum 1 year from date of sale
PACKAGE SIZE:	4 x 1 gallon jugs
.....	5 gallon pail
.....	55 gallon drum

rev. 01/12/21

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.