

SAFE STRIP
 SS-845
**SOLVENT AND WATERBORNE
 SEALER, COATING AND PAINT STRIPPER**

DESCRIPTION:

SAFE STRIP was developed to provide a more user and environmentally friendly stripper for solventborne and waterborne sealers and paints. SAFE STRIP contains no methylene chloride, is not flammable, and is without the other problems associated with petroleum solvents.

SAFE STRIP is safe to use on concrete, terrazzo (cementitious and resin-based), and masonry surfaces such as brick, natural stone, ceramic tile and quarry tile; it may also be used to strip wood floors down to bare wood. SAFE STRIP is not intended for use on, and will damage, synthetic resilient flooring such as vinyl composition tile, sheet vinyl, luxury vinyl tile and linoleum. If in doubt about using SAFE STRIP on a particular substrate, test in an inconspicuous area or consult SURTEC.


DIRECTIONS:

SAFE STRIP is ready-to-use and is not intended to be diluted with water. Depending on the profile or texture of the surface, apply SAFE STRIP using a mop, appropriate nap roller, or by spraying and then spreading with a deck brush. Work small areas at a time. SAFE STRIP can be very slippery underfoot, so proceed with caution if it is necessary to walk in treated areas. For solventborne and waterborne sealers and paints allow from at least 15 minutes to 1 hour dwell time, occasionally scrubbing or agitating with a floor buffer with a brush, or by hand with a deck brush. For higher performance two-part urethane coatings, 1 to 3 hours of dwell time may be necessary.

Before picking up the stripper solution, check a small area (~1 square foot) to ensure the seal has been completely removed. If not, allow SAFE STRIP to dwell longer with occasional scrubbing. In most cases, the stripped sealer solution cannot be vacuumed up directly, therefore, when ready for removal, add water or a dilute detergent solution to the surface, scrub into the stripper, and pick up or vacuum the stripper solution using a wet-dry vacuum. Scrub the stripped floor with SURTEC HC-150 diluted 2 oz. per gallon of water, followed by a thorough rinse with water. For wood surfaces, mop the floor several times using a tightly wrung mop with SURTEC NC-125 diluted 4 ounces per gallon. Allow the floor to dry, inspect for residue or unstripped sealer, and repeat the above procedures as necessary.

SPECIFICATIONS:

COLOR:	Lt. straw
ODOR:	Sweet, citrus
HMIS RATING	Health = 2 Flammability = 2 Physical Hazard = 0
VOC CONTENT	< 50% by weight
FLASH POINT:.....	140° F.
DILUTION RATE:.....	Ready to use
METHOD OF APPLICATION:	Solvent proof pump-up sprayer, mop, roller, deck brush
COVERAGE:	60 to 100 square feet per gallon
DWELL TIME:	15 minutes to 1 hour for paint, and waterborne and solventborne sealers
.....	1 to 3 hours for high performance, two-component coatings
BIODEGRADABLE:	Yes
pH:	N/A
SPECIFIC GRAVITY / DENSITY:	1.0 / 8.3 pounds per gallon
SOLUBILITY IN WATER:.....	Miscible
SHELF LIFE:.....	Minimum 1 year from date of sale
CONTAINER SIZES AVAILABLE:	4 x 1 gallon jugs
.....	5 gallon pail
.....	55 gallon drum

 **WARNING:** This product can expose you to chemicals including 1-Methyl-2-Pyrrolidone, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

rev. 01/12/21
 SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (209) 820-3700.