

# SCAN COMBIFLEX 330 / 330RS



The ScanCombiflex 330 (SC-330) is a powerful and easy to use machine, and is one of the most versatile machines on the market. The 330 mm / 13 inch single grinding disc is effective for grinding smaller areas, edging long stretches of the floor, lite coating removal and surface prep.

A simple and quick adjustment allows the operator to change the configuration of the SC-330 from a small grinder into an edger, with the entire process taking less than one minute.

The 330 mm / 13 inch disc on the SC-330 can be configured with 3, 6, or 9 of our metal, ceramic, or resin bond diamond tools. This allows the machine to cut more aggressively when necessary, or grind softer surfaces by spreading out the weight and using more tools.

For smooth and simple transport, the SC-330 can easily be separated into two parts, each weighing well under 100 lbs.

There are an optional 22.5 kg / 50 lbs weight available for SC 330. The weight kit only fits SC330 1-phase 110 V/230 V and SC330RS 1-phase 115 V.

The Scan Combiflex 330RS is equipped with adjustable speed.

## EASY ADJUSTMENT TO EDGE GRINDER



**GRINDING DISC**  
SINGLE



**GRINDING WIDTH**  
330 mm / 13"



**WEIGHT**  
65 kg (143 lbs) /  
70 kg / 154 lbs


# TECHNICAL DATA

## SCAN COMBIFLEX 330

	1-phase	3-phase
Voltage:	110-120 V 1~ or 220-240 V 1~	400 V 3~
Motor power:	1,5 kW	4 kW
Current:	20 Amp. or 10 Amp.	16 Amp.
Frequency:	60 Hz or 50 Hz	50-60 Hz
Grinding speed:	750 rpm or 600 rpm	1430 rpm
Grinding disc:	1 x 330 mm / 1 x 13"	1 x 330 mm / 1 x 13"
Grinding width:	330 mm / 13"	330 mm / 13"
Weight:	65 kg / 143 lbs.	65 kg / 143 lbs.
Other:	CE-marking	CE-marking

## SCAN COMBIFLEX 330RS

	1-phase	3-phase
Voltage:	110-120 V 1~ or 220-240 V 1~	400 V 3~
Motor power:	1,1 kW or 1,5 kW	4 kW
Current:	15 Amp. or 10 Amp.	16 Amp.
Frequency:	50-60 Hz	50-60 Hz
Grinding speed:	150-400 rpm or 250-750 rpm	250-1500 rpm
Grinding disc:	1 x 330 mm / 13"	1 x 330 mm / 13"
Grinding width:	330 mm / 13"	330 mm / 13"
Weight:	70 kg / 154 lbs.	70 kg / 154 lbs.
Other:	CE-marking	CE-marking



Weight kit available for SC330

Separates in two parts for easy transportation

SC330RS Variable speed and two directions

Adjustable head for edge grinding

Recommended vacuum SC330 and SC330RS: SD 2900 or SD3600

**SCANMASKIN**  
MACHINES-MINERALS-KNOW-HOW

Phone: +46 31 99 49 70  
Email: info@scanmaskin.com  
Website: www.scanmaskin.com