



PRO v2.0

| | |
|--|--|
| Chassis Construction: | 1/8" Steel (3.1 mm) Powder Coated |
| Front Wheels (Ø x Width): | 8" x 3" (20 x 7 cm) - Solid Grey, Non-Marking |
| Rear Wheels (Ø x Width): | (2x) 12" x 3" ((2x) 30 x 7 cm) - Solid Black |
| Size (L x W x H): | 53" x 31" x 57" (134 x 78 x 144 cm) |
| Weight (w/o Batteries): | 525 - 575 lbs (238 - 261 kg) |
| Weight (w/ Batteries): | 825 - 875 lbs (374 - 397 kg) |
| BRUSH / PAD SYSTEM | |
| Disk Dimensions: | 26" - (2x) 13" Ø (66 - [2x] 33 cm) 28" - (2x) 14" Ø (71 - [2x] 35 cm) |
| Disk Motor: | (2x) 0.75 hp ((2x) 551 watts) |
| Disk Brush Speed: | 270 rpm |
| Cylindrical Dimensions: | 25" - (2x) 6" Ø x 23" (64 - [2x] 15 x 58 cm) 29" - (2x) 6" Ø x 27" (73 - [2x] 15 x 68 cm) |
| Cylindrical Motor: | (2x) 0.75 hp (2x) 551 watts |
| Cylindrical Brush Speed: | 650 rpm Standard - 825 optional rpm |
| EDGE Dimensions: | 24" x 14" (60 x 35 cm) 28" x 14" (71 x 35 cm) |
| EDGE Motor: | 1.2 hp (882 watts) 2,500 rpm |
| Brush Down Pressure: | Up to 150 lbs (68 kg) / 500 lbs (227 kg) Actuator Rating |
| POWER SYSTEM | |
| System Voltage/Amps | 36 VDC / 175 ah WET |
| Optional Battery: | Up to 225 ah WET / 200 ah AGM* |
| *Includes Onboard Charger | |
| Run Time: | Up to 3.5 Hours** |
| **Based on continuous scrubbing run times. | |
| DRIVE SYSTEM | |
| Power: | 0.75 hp - All Gear / Sealed (559 watts) |
| Forward Speed: | 0 - 320 ft/min / 0 - 3.6 mph (0 - 98 m/min / 0 - 6 km/h) |
| Scrubbing Speed: | 0 - 256 ft/min / 0 - 2.9 mph (0 - 78 m/min / 0 - 5 km/h) |
| Reverse Speed: | 0 - 230 ft/min / 0 - 2.6 mph (0 - 70 m/min / 0 - 4 km/h) |
| SOLUTION / RECOVERY SYSTEMS | |
| Solution Tank Capacity: | 22 Gallons (83 liters) - w/ Graduated Site Tube |
| Solution Flow / Filter: | 0 - 0.5 GPM / Stainless Inline (0 - 2 LPM) |
| Recovery Tank Capacity: | 23 Gallons (87 liters) - 1.5" Ø Drain Hose |
| Demisting Chamber: | 1.25 Gallons (4.7 liters) |
| Drain Saver: | 130 cubic inches (2,130 cubic cm) |
| Vacuum Power | 1.0 hp / 2 Stage / 6.6" Ø (551 watts) |
| (Water Lift / Airflow): | 73" / 96 cfm (185 cm / 2.7 cm/m) |
| GENERAL | |
| Productivity - Theoretical: | Up to 40,000 sqft/hr (3,716 sqm)*** |
| ***Based off of ISSA 2010 Cleaning Times | |
| Productivity - Practical: | Up to 18,518 sqft/hr (1,720 sqm)*** |
| ***Based off of ISSA 2010 Cleaning Times | |



CRZ v2.0

| | |
|--|--|
| BODY CONSTRUCTION / DIMENSIONS | |
| Chassis Construction: | 3/16" Steel (4.8 mm) Powder Coated |
| Front Wheels (Ø x Width): | 10" x 3" (25 x 7 cm) - Solid Black |
| Rear Wheels (Ø x Width): | (2x) 12" x 3" ((2x) 30 x 7 cm) - Solid Black |
| Size (L x W x H): | 66" x 34" x 64" (167 x 86 x 162 cm) |
| Weight (w/o Batteries): | 725 lbs - 850 lbs (328 - 385 kg) |
| Weight (w/ Batteries): | 1,195 - 1,325 lbs (542 - 601 kg) |
| BRUSH / PAD SYSTEM | |
| Disk Dimensions: | 26" - (2x) 13" Ø (66 - [2x] 33 cm) 28" - (2x) 14" Ø (71 - [2x] 35 cm) 30" - (2x) 15" Ø (76 - [2x] 38 cm) 34" - (2x) 17" Ø (86 - [2x] 43 cm) |
| Disk Motor: | (2x) 0.75 hp ((2x) 551 watts) |
| Disk Brush Speed: | 270 rpm |
| Optional Motor Upgrade: | (2x) 1.5 hp 350 rpm ((2x) 1,103 watts) |
| Cylindrical Dimensions: | 25" - (2x) 6" Ø x 23" (63 - [2x] 15 x 58 cm) 29" - (2x) 6" Ø x 27" (73 - [2x] 15 x 68 cm) 33" - (2x) 6" Ø x 31" (83 - [2x] 15 x 78 cm) |
| Cylindrical Motor: | (2x) 0.75 hp ((2x) 551 watts) |
| Cylindrical Brush Speed: | 650 rpm Standard - 825 optional rpm |
| EDGE Dimensions: | 28" x 14" (71 x 35 cm) 32" x 14" (81 x 35 cm) |
| EDGE Motor: | 1.2 hp (882 watts) 2,500 rpm |
| Brush Down Pressure: | Up to 200 lbs (90 kg) / 500 lbs (227 kg) Actuator Rating |
| POWER SYSTEM | |
| System Voltage/Amps | 36 VDC / 210 ah WET |
| Optional Battery: | Up to 360 ah WET / 335 ah AGM* |
| *Includes Onboard Charger | |
| Run Time: | Up to 6 Hours** |
| **Based on continuous scrubbing run times. | |
| DRIVE SYSTEM | |
| Power: | 0.75 hp - All Gear / Sealed (559 watts) |
| Forward Speed: | 0 - 320 ft/min / 0 - 3.6 mph (0 - 98 m/min / 0 - 6 km/h) |
| Scrubbing Speed: | 0 - 256 ft/min / 0 - 2.9 mph (0 - 78 m/min / 0 - 5 km/h) |
| Reverse Speed: | 0 - 230 ft/min / 0 - 2.6 mph (0 - 70 m/min / 0 - 4 km/h) |
| SOLUTION / RECOVERY SYSTEMS | |
| Solution Capacity: | 33 Gallons (125 liters) - w/ Graduated Site Tube |
| Solution Flow / Filter: | 0 - 0.7 GPM / Stainless Inline (0 - 2 LPM) |
| Recovery Capacity: | 36 Gallons (136 liters) - 1.5" Ø Drain Hose |
| Demisting Chamber: | 1.25 Gallons (4.7 liters) |
| Drain Saver: | 130 cubic inches (2,130 cubic cm) |
| Vacuum Power | 1.0 hp / 2 Stage / 6.6" Ø (551 watts) |
| (Water Lift / Airflow): | 73" / 96 cfm (185 cm / 2.7 cm/m) |
| GENERAL | |
| Productivity - Theoretical: | Up to 47,000 sqft/hr (4,366 sqm)*** |
| ***Based off of ISSA 2010 Cleaning Times | |
| Productivity - Practical: | Up to 21,661 sqft/hr (2,012 sqm)*** |
| ***Based off of ISSA 2010 Cleaning Times | |



EX v2.0

| | |
|--|--|
| BODY CONSTRUCTION / DIMENSIONS | |
| Chassis Construction: | 3/16" Steel (4.8 mm) Powder Coated |
| Front Wheels (Ø x Width): | 10" x 3" (25 x 7 cm) - Solid Black |
| Rear Wheels (Ø x Width): | (4x) 12" x 3" ((2x) 30 x 7 cm) - Solid Black |
| Size (L x W x H): | 70" x 37" x 57" (177 x 93 x 144 cm) |
| Weight (w/o Batteries): | 790 lbs - 914 lbs (358 - 414 kg) |
| Weight (w/ Batteries): | 1,260 - 1,436 lbs (571 - 651 kg) |
| BRUSH / PAD SYSTEM | |
| Disk Dimensions: | 30" - (2x) 15" Ø (76 - [2x] 38 cm) 34" - (2x) 17" Ø (86 - [2x] 43 cm) 36" - (2x) 18" Ø (91 - [2x] 45 cm) |
| Disk Motor: | (2x) 1.5 hp 350 rpm ((2x) 1,103 watts) |
| Disk Brush Speed: | 350 rpm |
| Cylindrical Dimensions: | 29" - (2x) 6" Ø x 27" (73 - [2x] 15 x 68 cm) 33" - (2x) 6" Ø x 31" (83 - [2x] 15 x 78 cm) 37" - (2x) 6" Ø x 35" (94 - [2x] 15 x 89 cm) |
| Cylindrical Motor: | (2x) 1.5 hp 350 rpm ((2x) 1,103 watts) |
| Cylindrical Brush Speed: | 825 rpm |
| EDGE Dimensions: | N/A |
| EDGE Motor: | N/A |
| Brush Down Pressure: | Up to 225 lbs (102 kg) / 500 lbs (227 kg) Actuator Rating |
| POWER SYSTEM | |
| System Voltage/Amps | 36 VDC / 245 ah WET |
| Optional Battery: | Up to 360 ah WET / 335 ah AGM* |
| *Includes Onboard Charger | |
| Run Time: | Up to 5.5 Hours** |
| **Based on continuous scrubbing run times. | |
| DRIVE SYSTEM | |
| Power: | 1.0 hp - All Gear / Sealed (551 watts) |
| Forward Speed: | 0 - 320 ft/min / 0 - 3.6 mph (0 - 98 m/min / 0 - 6 km/h) |
| Scrubbing Speed: | 0 - 256 ft/min / 0 - 2.9 mph (0 - 78 m/min / 0 - 5 km/h) |
| Reverse Speed: | 0 - 230 ft/min / 0 - 2.6 mph (0 - 70 m/min / 0 - 4 km/h) |
| SOLUTION / RECOVERY SYSTEMS | |
| Solution Capacity: | 46 Gallons (174 liters) - w/ Graduated Site Tube |
| Solution Flow / Filter: | 0 - 0.7 GPM / Stainless Inline (0 - 2 LPM) |
| Recovery Capacity: | 49 Gallons (185 liters) - 1.5" Ø Drain Hose |
| Demisting Chamber: | 1.25 Gallons (4.7 liters) |
| Drain Saver: | 130 cubic inches (2,130 cubic cm) |
| Vacuum Power | 1.0 hp / 2 Stage / 6.6" Ø (551 watts) |
| (Water Lift / Airflow): | 73" / 96 cfm (185 cm / 2.7 cm/m) |
| GENERAL | |
| Productivity - Theoretical: | Up to 51,000 sqft/hr (4,738 sqm)*** |
| ***Based off of ISSA 2010 Cleaning Times | |
| Productivity - Practical: | Up to 23,627 sqft/hr (2,195 sqm)*** |
| ***Based off of ISSA 2010 Cleaning Times | |