

ULTRA 3
FP-541
ULTRA HIGH GLOSS FLOOR POLISH
ULTRA HIGH SPEED BUFFABLE

DESCRIPTION:

A new member of SURTEC's ULTRA series of floor polishes, ULTRA 3 combines innovative formulating with an advanced polymer system to create a floor polish which produces exceptional gloss, burnish response, durability and safety. ULTRA 3 produces optimum results when maintained by Ultra High Speed Buffing. ULTRA 3 offers exceptional leveling with superior surface adhesion and long-lasting shine. In addition to outstanding floor protection and appearance, a properly maintained ULTRA 3 floor can mean significant material and labor savings from a less frequent need to recoat or strip.

The superior adhesion of ULTRA 3 makes it the product of choice for all floor surfaces not affected by water including vinyl composition tile and sheet flooring, sealed concrete, terrazzo, ceramic tile, and sealed wood. ULTRA 3 is ideally suited for use in high speed maintenance programs, where a consistent, high level of gloss and appearance is required, such as in supermarkets and large retail stores. ULTRA 3 exceeds the Coefficient of Friction safety standards of ASTM Designation D-2047.

DIRECTIONS:

APPLICATION - Use standard application procedures with a good quality rayon or synthetic blend string mop taking great care to apply only thin to medium coats. Upon drying, high speed buff the last coat applied for optimum results. High speed buffing ULTRA 3 will prolong the life of the polish and increase safety and durability, as well as increase shine and appearance. A propane buffer equipped with THERMAL GLOSS pads will achieve excellent buffing results, but any good quality high speed (1000+ rpm) buffer will achieve suitable results.

ROUTINE MAINTENANCE - Use SURTEC LF-150 heavy duty floor cleaner or FLOOR SHINE High Speed Floor Maintainer at 1 or 2 ozs. per gallon of water for damp mopping or scrubbing prior to high-speed buffing.

RECOAT - Scrub the floor with a low speed buffer or automatic scrubber and blue or green (medium scrub) pads using LF-150 Heavy Duty Cleaner at a dilution of 2 to 4 ozs. per gallon of water to achieve a clean surface. Rinse the floor with clean water and let dry, then apply one or more coats of ULTRA 3, allowing each coat to dry completely before applying the next coat. Upon drying, high speed buff the last coat applied for optimum results.

STRIPPING - If stripping is necessary, use SURTEC L.O.S., SUPER STRIP or ULTRA STRIP according to label directions.

SPECIFICATIONS:

COLOR:	Milk white, stable emulsion, dries clear
ODOR:	Sweet
pH:	9.0 ± 0.2
SPECIFIC GRAVITY/DENSITY:	1.03 / 8.6 pounds per gallon
FLASH POINT:	None (C.O.C. Method)
VOC CONTENT:	Less than 1% by weight
HMIS RATING:	Health = 1 Flammability = 0 Physical Hazard = 0
REFRACTOMETER SOLIDS:	28%
GLOSS:	98 (A.S.T.M. Test D-523, 60°)
DRYING TIME:	20 - 30 minutes at 20°C. (68°F.), 50% relative humidity
COVERAGE:	2000 sq. ft. per gallon (average coverage on a sealed floor)
LEVELING:	Excellent (A.S.T.M. Test D-2801)
POWDERING RESISTANCE:	Excellent (A.S.T.M. Test D-2048-82)
RECOATABILITY:	Excellent (A.S.T.M. Test D-3153-78)
SAFETY (slip resistance):	Exceeds requirements (A.S.T.M. Test D-2047)
PACKAGE SIZES:	4 x 1 gallon jugs
.....	5 gallon Twin Pack (2 x 2.5 gal. bottles/box)
.....	55 gallon drums